

DECLARATION OF PERFORMANCE

DoP No. 0679-CPD-0382
(alternative CPD No. 0679-CPD-0383)
(alternative CPD No. 0679-CPD-0614)

1. Unique identification code of the product-type:

Powers Ceiling Anchor PBZ-PRO

Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

ETA-09/0011

Batch number: see packaging of the product.

Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

generic type	Deformation controlled expansion anchor, sizes 6 mm
for use in	Uncracked and cracked concrete, C20/25 to C50/60 acc. to EN 206 The anchor may be used for redundant systems or multiple use systems for non structural applications only.
option / category	ETAG 001-6, redundant systems
loading	Static and quasi-static, Fire (TR020)
material	galvanized steel, dry internal conditions only covered size: 6 mm
temperature range	Not applicable

2. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Product name: PBZ-PRO

Powers Fasteners Europe B.V.
Stanley Black & Decker Deutschland GmbH
Black-&-Decker Str. 40
65510 Idstein
Germany

3. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2): --
4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 2+**
5. In case of the declaration of performance concerning a construction product covered by a harmonised standard: --
6. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:
Centre Scientifique et Technique du Bâtiment CSTB Paris issued: ETA-09/0011
on the basis of **ETAG 001-6**, redundant systems

The notified body 0679-CPD performed certification of factory production control on the basis of:

- initial inspection of factory and of factory production control;
- continuous surveillance, assessment and approval of factory production control.

9. Declared performance:

Essential Characteristics	Design Method	Performance	Harmonized Technical Specification
characteristic resistance for tension	ETAG 001, Annex A, method C	ETA-09/0011, annex 3	ETAG 001-6
characteristic resistance for shear	ETAG 001, Annex A, method C	ETA-09/0011, annex 3	
minimum spacing and minimum edge distance	ETAG 001, Annex A, method C	ETA-09/0011, annex 2	
displacement for serviceability limit state	ETAG 001, Annex A, method C	Not applicable	

Where pursuant to Article 37 or 38 in the Specific Technical Documentation has been used, the requirements with which the product complies: --

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



Colin Earl
VP HTF CDIY Europe



Dr. Ing. Thilo Pregartner
Senior Engineering Manager

